

IN THE CLAIMS:

1. (Currently Amended) A system for automatically initiating a subsequent telephone call over a computer network from a second caller to a first caller, comprising:

an address interceptor, associated with a station of a circuit-switched telephone network, that receives calling number identification signals of said first caller from a first telephone call from said first caller to said second caller over said circuit-switched telephone network and extracts from said calling number identification signals ~~first telephone call~~ a destination address of said first caller for said[[a]] subsequent telephone call from said second caller to said first caller; and

a network call initiator, coupled to said address interceptor and associated with a computer network terminal, that employs said destination address of said first caller to automatically initiate said subsequent telephone call to said destination address via said computer network terminal.

2. (Original) The system as recited in Claim 1 wherein said calling number identification signals and said destination address are associated with a single location.

3. (Original) The system as recited in Claim 1 wherein said destination address is selected from the group consisting of:

a telephone number,

an Internet Protocol address,

a Voice over Internet Protocol (VoIP) gateway address, and

a VoIP gateway address combined with a telephone number.

4. (Original) The system as recited in Claim 1 wherein said computer network is the Internet.

5. (Original) The system as recited in Claim 1 wherein said station leaves unanswered a call transmitting said calling number identification signals.

6. (Original) The system as recited in Claim 1 wherein said calling number identification signals are associated with a second station, said second station hanging up after a predetermined number of unanswered rings.

7. (Original) The system as recited in Claim 1 wherein said station and said computer network terminal are embodied in a computer and wherein a single telephone line alternatively couples said station to said circuit-switched telephone network and said computer network terminal to said computer network.

8. (Currently Amended) A method of automatically initiating a subsequent telephone call over a computer network from a second caller to a first caller, comprising:

extracting a destination address for said[[a]] subsequent telephone call from calling number identification signals received from a first telephone call over a circuit-switched telephone network

from said first caller to said second caller; and

employing said destination address of said first caller to automatically initiate said subsequent telephone call to said destination address via said computer network.

9. (Original) The method as recited in Claim 8 wherein said calling number identification signals and said destination address are associated with a single location.

10. (Original) The method as recited in Claim 8 wherein said destination address is selected from the group consisting of:

a telephone number,

an Internet Protocol address,

a Voice over Internet Protocol (VoIP) gateway address, and

a VoIP gateway address combined with a telephone number.

11. (Original) The method as recited in Claim 8 wherein said computer network is the Internet.

12. (Original) The method as recited in Claim 8 further comprising leaving unanswered a call transmitting said calling number identification signals.

13. (Original) The method as recited in Claim 8 wherein said calling number

identification signals are associated with a station, said method further comprising hanging up said station after a predetermined number of unanswered rings.

14. (Original) The method as recited in Claim 8 wherein said method is carried out in a computer and wherein a single telephone line alternatively carries said calling number identification signals and said destination address.

15. (Currently Amended) A computer, comprising:

- a processor;
- a memory coupled to said processor;
- a display coupled to said processor;
- at least one input device coupled to said processor;
- a circuit-switched telephone network interface, coupled to said processor, for receiving a first telephone call from a first caller over a circuit-switched telephone network couplable thereto, said first telephone call including calling number identification signals;
- a computer network interface, coupled to said processor, for allowing said computer to communicate over a computer network;
- an address interceptor, coupled to said processor and communicable with said circuit-switched telephone network interface, for extracting a destination address of said first caller for a subsequent telephone call to said first caller from said calling number identification signals; and
- a network call initiator, coupled to said processor, for employing said destination address

of said first caller to automatically initiate said subsequent telephone call to said destination address of said first caller via said computer network interface.

16. (Original) The computer as recited in Claim 15 wherein said calling number identification signals and said destination address are associated with a single location.

17. (Original) The computer as recited in Claim 15 wherein said destination address is selected from the group consisting of:

a telephone number,

an Internet Protocol address,

a Voice over Internet Protocol (VoIP) gateway address, and

a VoIP gateway address combined with a telephone number.

18. (Original) The computer as recited in Claim 15 wherein said computer network is the Internet.

19. (Original) The computer as recited in Claim 15 wherein said circuit-switched telephone network interface leaves said call unanswered.

20. (Original) The computer as recited in Claim 15 wherein a station placing said call hangs up after a predetermined number of unanswered rings.

21. (Original) The computer as recited in Claim 15 wherein said circuit-switched telephone network interface and said computer network interface are coupled to a single telephone line.